

Philips  
Stereo Dubbing Cable

6 ft

3.5 mm(M) - 3.5 mm(M)

SWA2162



## Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

### Enjoy good audio quality

- Nickel-plated connectors for reliable contact
- High purity copper conductor for reliable signal transfer

### Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

### Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket

### Protects against signal loss

- Bare copper shielding

**PHILIPS**  
sense and simplicity

Stereo Dubbing Cable  
6 ft 3.5 mm(M) - 3.5 mm(M)

# Specifications

## Packaging

- EAN/UPC/GTIN: 6 09585 13968 8
- Quantity: 1
- Gross Weight: 0.086 kg
- Tare Weight: 0.010 kg
- Net Weight: 0.076 kg
- Length: 19.70 cm
- Width: 10.80 cm
- Height: 2.50 cm

## Inner Carton

- EAN/UPC/GTIN: 1 06 09585 13968 5
- Quantity: 6
- Gross Weight: 0.517 kg
- Tare Weight: 0.061 kg

- Net Weight: 0.456 kg
- Length (cm): 27.80 cm
- Width (cm): 9.20 cm
- Height (cm): 12.70 cm

## Outer Carton

- EAN/UPC/GTIN: 2 06 09585 13968 2
- Quantity: 72
- Gross Weight: 6.205 kg
- Tare Weight: 0.733 kg
- Net Weight: 5.472 kg
- Length (cm): 46.50 cm
- Width (cm): 37.90 cm
- Height (cm): 26.30 cm

SWA2162/17

# Highlights

## Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

## Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

## Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

## Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

## High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

## Bare copper shielding

Bare copper shielding protects against signal loss.

## Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.



Issue date 2009-03-09

Version: 1.1.4

12 NC: 8670 000 32602  
UPC: 6 09585 13968 8

© 2009 Koninklijke Philips Electronics N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips  
Electronics N.V. or their respective owners.

[www.philips.com](http://www.philips.com)